

NANLUX

***Evoke 2400B* DMX REFERENCE GUIDE**

This DMX reference guide has been compiled according to the rigorous testing for Nanlux products. Product designs are subject to change without prior notice. The latest version of this guide is downloadable at www.nanlux.com.

CCT 8bit

CHANNEL	VALUE	%	FUNCTION	NOTES
1	0-255	0-100	DIMMER 0.0% to 100.0%	
2	0-255	0-100	CCT 2700K-6500K	
3	0-10 11-20 21-99 100-165 166-244 245-255	0-4 5-8 9-47 48-57 58-96 97-100	GREEN/MAGENTA Neutral/No Effect -80 Green -79 to -1 Green Neutral/No Effect +1 to +79 Green +80 Green	
4	0-255	0-100	ZOOM Min. to Max. Beam Angle	
5-6			RESERVED	

When "DMX Reduced Channels" is ON, the following channels are reduced in all DMX modes except ULTIMATE DMX MODE.

CHANNEL	VALUE	%	FUNCTION	NOTES
7	0-63 64-127 128-191 192-255	0-25 26-50 51-75 76-100	SMART FULL SPEED HALF SPEED FAN OFF	
8	0-3 4 5 6 7-255	0-1.2 1.6 2.0 2.4 2.7-100	STROBE OFF Random Fast Random Medium Random Slow Variable Strobe(0.4Hz --> 25Hz)	
9-10			RESERVED	

CCT 16bit

CHANNEL	VALUE	%	FUNCTION	NOTES
1-2	0-65535	0-100	DIMMER 0.0% to 100.0%	
3-4	0-65535	0-100	CCT 2700K-6500K	
5-6	0-5000 5001-10000 10001-29999 30000-40000 40001-59999 60000-65535	0-4 5-8 9-47 48-57 58-96 97-100	GREEN/MAGENTA Neutral/No Effect -80 Green -79 to -1 Green Neutral/No Effect +1 to +79 Green +80 Green	
7	0-255	0-100	ZOOM Min. to Max. Beam Angle	
8-9			RESERVED	

When "DMX Reduced Channels" is ON, the following channels are reduced in all DMX modes except ULTIMATE DMX MODE.

CHANNEL	VALUE	%	FUNCTION	NOTES
10	0-63 64-127 128-191 192-255	0-25 26-50 51-75 76-100	SMART FULL SPEED HALF SPEED FAN OFF	
11	0-3 4 5 6 7-255	0-1.2 1.6 2.0 2.4 2.7-100	STROBE OFF Random Fast Random Medium Random Slow Variable Strobe(0.4Hz --> 25Hz)	
12-15			RESERVED	

ULTIMATE DMX 8bit-CCT MODE

CHANNEL	VALUE	%	FUNCTION	NOTES
1	0-255	0-100	DIMMER 0.0% to 100.0%	
2	0-63 64-127 128-255	0-25 26-50 51-100	MODE CCT EFFECT RESERVED	0 ≤ value ≤ 63
3	0-255	0-100	CCT	2700K-6500K
4	0-10 11-20 21-99 100-165 166-244 245-255	0-4 5-8 9-47 48-57 58-96 97-100	GREEN/MAGENTA Neutral/No Effect -80 Green -79 to -1 Green Neutral/No Effect +1 to +79 Green +80 Green	
5-11			N/A	
12	0-255	0-100	ZOOM Min. to Max. Beam Angle	
13-14			RESERVED	
15	0-63 64-127 128-191 192-255	0-25 26-50 51-75 76-100	SMART FULL SPEED HALF SPEED FAN OFF	

ULTIMATE DMX 8bit-EFFECT MODE

CHANNEL	VALUE	%	FUNCTION	NOTES
1	0-255	0-100	DIMMER 0.0% to 100.0%	
2	0-63 64-127 128-255	0-25 26-50 51-100	MODE CCT EFFECT RESERVED	64 ≤ value ≤ 127
3	0-18 19-36 37-54 55-72 73-90 91-108 109-126 127-144 145-162 163-180 181-198 199-216 217-255	0-7 8-14 15-21 22-28 29-35 36-42 43-50 51-57 58-64 65-71 72-78 79-85 86-100	EFFECT MODE CCT LOOP INT LOOP FLASH PULSE STORM TV PAPARAZZI CANDLE/FIRE BAD BULB FIREWORK EXPLOSION WELDING RESERVED	
4	0-255	0-100	DMX EFFECTS PARAMETER #1	See DMX Effects chart
5	0-255	0-100	DMX EFFECTS PARAMETER #2	See DMX Effects chart
6	0-255	0-100	DMX EFFECTS PARAMETER #3	See DMX Effects chart
7	0-255	0-100	DMX EFFECTS PARAMETER #4	See DMX Effects chart
8	0-255	0-100	DMX EFFECTS PARAMETER #5	See DMX Effects chart
9	0-255	0-100	DMX EFFECTS PARAMETER #6	See DMX Effects chart
10	0-255	0-100	DMX EFFECTS PARAMETER #7	See DMX Effects chart
11	0-255	0-100	DMX EFFECTS PARAMETER #8	See DMX Effects chart
12	0-255	0-100	ZOOM Min. to Max. Beam Angle	
13-14			RESERVED	
15	0-63 64-127 128-191 192-255	0-25 26-50 51-75 76-100	SMART FULL SPEED HALF SPEED FAN OFF	

DMX EFFECT CHART

EFFECT	CCT LOOP 0 ≤ value ≤ 18			
CH4/PARAMETER #1	CCT HIGH			
CH5/PARAMETER #2	CCT LOW			
CH6/PARAMETER #3	G/M			
CH7/PARAMETER #4	SPEED			
CH8/PARAMETER #5	CYCLE:ONE WAY = 0-85(0%-33%) CYCLE:TWO WAY = 86-170(34%-66%) CYCLE:REVERSE = 171-255(67%-100%)			
CH9/PARAMETER #6	ADD-ON:OFF = 0-63(0%-25%)	ADD-ON:FLASH = 64-127(26%-50%)	ADD-ON:RANDOM FLASH = 128-191(51%-75%)	ADD-ON:PULSE = 192-255(76%-100%)
CH10/PARAMETER #7	N/A	INTERVALS	SPEED	PULSES/MIN
CH11/PARAMETER #8	N/A	FLASH RATIO	N/A	N/A

DMX EFFECT CHART

EFFECT	INT LOOP 19 ≤ value ≤ 36			
CH4/PARAMETER #1	DIM LOW			
CH5/PARAMETER #2	CCT			
CH6/PARAMETER #3	G/M			
CH7/PARAMETER #4	SPEED			
CH8/PARAMETER #5	CYCLE:ONE WAY = 0-85(0%-33%) CYCLE:TWO WAY = 86-170(34%-66%) CYCLE:REVERSE = 171-255(67%-100%)			
CH9/PARAMETER #6	ADD-ON:OFF = 0-63(0%-25%)	ADD-ON:FLASH = 64-127(26%-50%)	ADD-ON:RANDOM FLASH = 128-191(51%-75%)	ADD-ON:PULSE = 192-255(76%-100%)
CH10/PARAMETER #7	N/A	INTERVALS	SPEED	PULSES/MIN
CH11/PARAMETER #8	N/A	FLASH RATIO	N/A	N/A

DMX EFFECT CHART

EFFECT	FLASH 37 ≤ value ≤ 54	
CH4/PARAMETER #1	CCT	
CH5/PARAMETER #2	G/M	
CH6/PARAMETER #3	INTERVALS	
CH7/PARAMETER #4	FLASH RATIO	
CH8/PARAMETER #5	PAUSE: OFF = 0-127(0%-50%)	PAUSE: ON = 128-255(51%-100%)
CH9/PARAMETER #6	N/A	
CH10/PARAMETER #7	N/A	
CH11/PARAMETER #8	N/A	

DMX EFFECT CHART

EFFECT	PULSE 55 ≤ value ≤ 72	
CH4/PARAMETER #1	CCT	
CH5/PARAMETER #2	G/M	
CH6/PARAMETER #3	PULSES/MIN	
CH7/PARAMETER #4	N/A	
CH8/PARAMETER #5	N/A	
CH9/PARAMETER #6	N/A	
CH10/PARAMETER #7	N/A	
CH11/PARAMETER #8	N/A	

DMX EFFECT CHART

EFFECT	STORM 73 ≤ value ≤ 90		
CH4/PARAMETER #1	CCT		
CH5/PARAMETER #2	FLASH TIMES HIGH		
CH6/PARAMETER #3	FLASH TIMES LOW		
CH7/PARAMETER #4	TRIGGER: AUTO = 0-127(0%-50%)	TRIGGER: MANUAL = 128-255(51%-100%)	
CH8/PARAMETER #5	INTERVAL HIGH	Trigger: OFF = 0-127(0%-50%)	Trigger: ON = 128-255(51%-100%)
CH9/PARAMETER #6	INTERVAL LOW	N/A	
CH10/PARAMETER #7	PAUSE: OFF = 0-127(0%-50%)	PAUSE: ON = 128-255(51%-100%)	N/A
CH11/PARAMETER #8	N/A		

DMX EFFECT CHART

EFFECT	TV 91 ≤ value ≤ 108
CH4/PARAMETER #1	DIM LOW
CH5/PARAMETER #2	CCT
CH6/PARAMETER #3	G/M
CH7/PARAMETER #4	CCT SHIFT
CH8/PARAMETER #5	SPEED
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A
CH11/PARAMETER #8	N/A

DMX EFFECT CHART

EFFECT	PAPARAZZI 109 ≤ value ≤ 126
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	G/M
CH6/PARAMETER #3	SPEED
CH7/PARAMETER #4	N/A
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A
CH11/PARAMETER #8	N/A

DMX EFFECT CHART

EFFECT	CANDLE/FIRE 127 ≤ value ≤ 144
CH4/PARAMETER #1	DIM LOW
CH5/PARAMETER #2	CCT
CH6/PARAMETER #3	G/M
CH7/PARAMETER #4	CCT SHIFT
CH8/PARAMETER #5	SPEED
CH9/PARAMETER #6	FLICKER: OFF = 0-127(0%-50%) FLICKER: ON = 128-255(51%-100%)
CH10/PARAMETER #7	N/A
CH11/PARAMETER #8	N/A

DMX EFFECT CHART

EFFECT	BAD BULB 145 ≤ value ≤ 162
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	G/M
CH6/PARAMETER #3	INTENSITY
CH7/PARAMETER #4	SPEED
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A
CH11/PARAMETER #8	N/A

DMX EFFECT CHART

EFFECT	FIREWORK 163 ≤ value ≤ 180
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	G/M
CH6/PARAMETER #3	CCT SHIFT
CH7/PARAMETER #4	SPEED
CH8/PARAMETER #5	DECAY
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A
CH11/PARAMETER #8	N/A

DMX EFFECT CHART

EFFECT	EXPLOSION 181 ≤ value ≤ 198	
CH4/PARAMETER #1	CCT	
CH5/PARAMETER #2	G/M	
CH6/PARAMETER #3	DECAY	
CH7/PARAMETER #4	TRIGGER: AUTO = 0-127(0%-50%)	TRIGGER: MANUAL = 128-255(51%-100%)
CH8/PARAMETER #5	SPEED	Trigger: OFF = 0-127(0%-50%) Trigger: ON = 128-255(51%-100%)
CH9/PARAMETER #6	N/A	
CH10/PARAMETER #7	N/A	
CH11/PARAMETER #8	N/A	

DMX EFFECT CHART

EFFECT	WELDING 199 ≤ value ≤ 216
CH4/PARAMETER #1	DIM LOW
CH5/PARAMETER #2	CCT
CH6/PARAMETER #3	G/M
CH7/PARAMETER #4	SPEED
CH8/PARAMETER #5	PAUSE: OFF = 0-127(0%-50%) PAUSE: ON = 128-255(51%-100%)
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A
CH11/PARAMETER #8	N/A

NANLUX

Guangdong NanGuang Photo&Video Systems Co.,Ltd.

☎ +86-754-85751187

☎ +86-754-85300887

✉ info@nanlux.com

<http://www.nanlux.com>

📍 Dongli Section, Highway 324, Chenghai, Shantou City, Guangdong Province, China